ORISTREAK LTD.





PRODUCT LIST – IC PRODUCT

•LED Driver IC (GREEN PRODUCT) •HY2821

Operation 5~40V SOT23 5-pin small package.

·HY3010

Operation 3V~40V Output switching current to 1A. SOT-23 6-pin small package.

•HY3015

Operation 3V~40V Output switching current to 1A TO252-5L 5-pin Power package

•HY7700

Operation 9V~450V Constant Current LED driver controller PWM Low-Frequency Dimming Input Voltage Surge ratings up to 450V SOP-8L 8-Pin SOP Package











PRODUCT LIST – IC PRODUCT

•LED Driver IC (GREEN PRODUCT) •HY7701B

Operation 9V~600V
Constant Current LED driver controller
PWM Low-Frequency Dimming
Fixed frequency or fixed off-time operation
Input Voltage Surge ratings up to 600V
SOP-8L 8-Pin SOP Package



•HY7731

Operation 8V~450V
Constant Current LED driver controller
PWM Low-Frequency Dimming
Fixed frequency or fixed off-time operation
Input Voltage Surge ratings up to 450V
Unity power factor
SOP-8L 8-Pin SOP Package.






PRODUCT LIST – IC PRODUCT

•VOLTAGE REGULATOR IC (GREEN PRODUCT)

•HY2596

Operation 5V~40V
Switch Mode Step-down Voltage Regulator
3A Output Current ability
5V & Adjustable Output Voltage
150KHz Fixed Frequency
Regulates Positive or Negative output voltage.
ESOP-8L 8-Pin SOP Package
TO263-5L Power Package



•HY5171

Operation 2.7V~30V
Switch Mode Step-up Voltage Regulator
Integrated Power Switch 1.5A
External Synchronization
Regulates Positive or Negative output voltage.
SOP-8L 8-Pin SOP Package.





PRODUCT SELECTOR GUIDES

LED Driver IC

Device	Topology	VIN		Output Current	Dimming	Package Option
Device		min(V)	max(V)	(mA)	Diffilling	rackage Option
HY3010	PFM	3	40	1000	PWM	SOT-23-6L
1113010	BUCK					
HY3015	PWM	3	40	1 500	External Circuit	TO252-5L
1113013	BUCK					
HY7700	PFM · PWM	9	450	External FET	PWM Linear	SOIC-8L
1117700	BUCK · BUCK-BOOST					
HY7701B	PFM · PWM	10	600	External FET	PWM Linear	SOIC-8L
11177010	BUCK · BUCK-BOOST					
HY7731	Single-Switch PFC	8	450	External FET	PWM	SOIC-8L

Voltage Regulator IC

Device	Topology	V	IN	Current Ability	ENABLE	Package Option
Device		min(V)	max(V)	(mA)		
HY2596	PWM	_	40	3000	PWM	SOT-23-6L
H12390	BUCK	7 3				TO263-5L
HY5171	PWM	2.7	30	1500	External Synchronization	SOIC-8L
1113171	BOOST · SEPIC	2.7				

Other IC

	Device	FUNCTION	VIN		Current Ability	ENABLE	Package Option
			min(V)	max(V)	(mA)	ENABLE	rackage Option
I	HY2821	Power LED Driver tool.	5	40	External Regulator	N/A	SOT-23-5L

