

Triaxial Specifications:

- 1.Triaxial
- 2.Impedance: 50 ± 2 ohm
- 3.Operating Voltage: 1000 VRMS/2000VOC
- 4.最小漏電流：100fA
- 5.Frequency range 頻寬:300 MHZ
- 6.Maximum current: 10A
- 7.長度客製化

Triaxial Cable Type:

- 1.Triaxial(公) to Triaxial(公)-Cable
- 2.Triaxial(公) to 裸線-Cable
- 3.Triaxial(公) to Triaxial(母)-Cable
- 4.Triaxial(公) to 杜邦端子(母)-Cable
- 5.Triaxial(公) to Banana(母)-Cable
- 6.Triaxial(公) to Banana(公)-Cable
- 7.Triaxial(公) to 鱷魚夾-Cable
- 8.Triaxial(公) to 測試勾-Cable
- 9.Triaxial(公) to BNC(母)-Cable
- 10.Triaxial(公) to BNC(公)-Cable
- 11.Triaxial(公) to SMA(公)-Cable
- 12.Triaxial(公) to SMA(母)-Cable







Triaxial(公) to 3測試勾(signal+guard+ground)-Cable



Triaxial(公) to BNC(公)-Cable



Triaxial (公) to BNC(母)-Cable

































