

SHE 雄鑫電子

Super High-tech Electric Co., Ltd.

LED Lighting



SUPER HIGH-TECH ELECTRIC CORPORATION



LED Projection Lamp 40W

LED 投射燈 40W

Standard Housing Color: White, Black, Red, Yellow Green
or customized request

Including Power Supply Model HLG-60H-30A



Specifications:

CE IP65 CNS

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		15		ea	High Power Cree LED
Operation Voltage	45		50	V _{DC}	Constant Current 760 mA
Ambient Temperature	-20		40	°C	
Power Consumption		40		Watt	
Illumination		3000		Lm	Color Temp : 4750~5300K
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		30000		hours	
Weight		2400		g	
Outline dimension(mm)	270 × 55.6 × 252.4 (L × W × H)				



LED Projection Light 60W

投射燈 60W

Standard Housing Color:

White, Black, Red, Yellow Green or customized request

Including Power Supply Model HLG-60H-30A



電源供應器(power supply)

Specifications:

IP65

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		9		ea	High Power Cree LED
Operation Voltage	27		30	V _{DC}	Constant Current 2000mA
Ambient Temperature	-20		40	°C	
Power Consumption		60		Watt	
Illumination		4800		Lm	Cool White: 5500~6500K
		4000			Warm White: 2600K~3700K
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		40000		hours	
Weight		2400		g	
Outline dimension(mm)	270 × 55.6 × 252.4 (L × W × H)				



LED Projection Lamp 35~40W

LED 工作燈 35~40W

Standard Housing Color: White,
Black, Red, Yellow Green
or customized request
Including Power Supply & Tripod



Specifications:

IP65

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		15		ea	High Power Cree LED
Operation Voltage	45		50	V _{DC}	Constant Current 760mA
Ambient Temperature	-20		40	°C	
Power Consumption		40		Watt	
Illumination		3000		Lm	Cool White: 5500K~6500K
		2500			Warm White: 2600K~3700K
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		30,000		hours	
Weight		2,400		g	
Outline dimension(mm)	270 × 55.6 × 252.4 (L × W × H)				




LED High Bay Light 120W

天井燈 120W

Standard Housing Color: White, Black, Red or customized request
Including Power supply



Light Distribution:



Specifications:

IP65

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		18		ea	High Power Cree LED
Operation Voltage	56		60	V _{DC}	2000mA
Ambient Temperature	-20		40	°C	
Power Consumption		120		Watt	
Illumination		9600		Lm	Cool White: 5500~6500K
		8000			Warm White: 2600K~3700K
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		40000		hours	
Weight		5000		g	
Outline dimension(mm)	375 × 270 × 150 (L × W × H)				



LED High Bay Light 70W

LED 高效能天井燈 70W

Lamp Head Type:

E39/ E40 & Hook(compatible with E39/ E40)

Including Safety rope



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		10		ea	High Power Cree LED
Operation Voltage	30		32	V _{DC}	Constant Current 2100mA
Ambient Temperature	-20		40	°C	
Power Consumption		70		Watt	
Illumination		5500		Lm	Warm White: 2600~3700K
		4600			Cool White: 5000K~6500K
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		40000		hours	
Weight		3000		g	
Outline dimension(mm)	336 × 250 (H × D)				



PAR 38 LED Light

PAR 38

Standard Housing Color: Silver



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		12		ea	
Operation Voltage	36		43	V _{DC}	Constant Current 400mA
Ambient Temperature	-20		40	°C	
Power Consumption		18		Watt	
Illumination		1000		Lm	Warm White : 2850~3050K
LED Viewing Angle		110		Degree	
CRI		77			
LED Life time		30,000		hours	
Weight		400		g	
Outline dimension(mm)	130 × 120 (H × D)				



10W LED Bulb

10W LED 燈泡

10W Black

10W Silver

Color Black treated by Nano Anodizing



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		18		ea	High Power LED
Operation Voltage	56		60	V _{DC}	Constant Current 150mA
Ambient Temperature	-20		40	°C	
Power Consumption		10		Watt	
Illumination		750		Lm	Cool White: 5700K
			Warm White: 3000K		
LED Viewing Angle		110		Degree	
CRI		82			
LED Life time		30,000		hours	
Weight		150		g	
Outline dimension(mm)	134.1 × 65.2 (H × D)				



LED Bulb 6W / 9W E27

LED 球泡燈 6W/9W

6W

9W

Standard Housing Color: White



6W Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		12		ea	
Operation Voltage	36		40	V _{DC}	Constant Current 135mA
Ambient Temperature	-20		40	°C	
Power Consumption		6		Watt	
Illumination		450		Lm	Cool White: 5700K
			Warm White: 3000K		
LED Viewing Angle		110		Degree	
CRI		82			
LED Life time		30,000		hours	
Weight		155		g	
Outline dimension(mm)	117.4 × 60 (H × D)				

9W Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		18		ea	
Operation Voltage	56		60	V _{DC}	Constant Current 135mA
Ambient Temperature	-20		40	°C	
Power Consumption		9		Watt	
Illumination		650		Lm	Cool White: 5700K
			Warm White: 3000K		
LED Viewing Angle		110		Degree	
CRI		82			
LED Life time		30,000		hours	
Weight		155		g	
Outline dimension(mm)	117.4 × 60 (H × D)				



LED Bulb 9W / E27

LED 陶瓷球泡燈

Standard Housing Color: Silver Gray



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		20		ea	
Operation Voltage	30		33	V _{DC}	Constant Current 270mA
Ambient Temperature	-20		40	°C	
Power Consumption		9		Watt	
Illumination		700		Lm	Cool White: 6200K
			Warm White: 3000K		
LED Viewing Angle		110		Degree	
CRI		70			
LED Life time		30,000		hours	
Weight		150		g	
Outline dimension(mm)	125.4 × 60 (H × D)				



LED Bulb MR 16

LED 燈泡 MR16

5W GU5.3

Standard Housing Color: Black & Silver



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		1		ea	
Operation Voltage	6		8	V _{DC}	Constant Current 600mA
Ambient Temperature	-20		40	°C	
Power Consumption		5		Watt	
Illumination		240		Lm	Warm White : 2850~3050K
LED Viewing Angle		110		Degree	
CRI		77			
LED Life time		30,000		hours	
Weight		40		g	
Outline dimension(mm)	50 × 49 (H × D)				



LED Bulb GU10

LED 燈泡 GU10

4W GU 10

Standard Housing Color: Silver



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		3		ea	
Operation Voltage	9		10	V _{DC}	Constant Current 350mA
Ambient Temperature	-20		40	°C	
Power Consumption		4		Watt	
Illumination		240		Lm	Warm White : 2850~3050K
LED Viewing Angle		110		Degree	
CRI		77			
LED Life time		30,000		hours	
Weight		40		g	
Outline dimension(mm)	50 × 49 (H × D)				



LED Bulb 3W/E27

LED 球泡燈

Standard Housing Color: White




Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		6		ea	
Operation Voltage		9.6		V _{DC}	Constant Current 300mA
Ambient Temperature	-20		40	°C	
Power Consumption		3		Watt	
Illumination		200		Lm	Cool White: 5700K
			Warm White: 3000K		
LED Viewing Angle		110		Degree	
CRI		82			
LED Life time		30,000		hours	
Weight		80		g	
Outline dimension(mm)	100 × 52 (H × D)				



LED T8 Tube Light

LED T8 日光燈



Specifications:

Parameter	T8-10W	T8-18W
Size(mm)	T8/30*578mm	T8/30*1198mm
Power(Watt)	10W	18W
Input Voltage(V)	AC220/110V	AC220/110V
Luminous Flux(Lm)	800	1600
CRI	≥70	≥70
PF	≥0.917	≥0.917
Color Temperature	5700~6300K	5700~6300K
Light Color	Cool white	Cool white
Beam Angle(Degree)	120°	120°
Material of Housing	Aluminum Alloy/PC Cover	Aluminum Alloy/PC Cover
Lifespan(Hours)	≥20000/hr	≥20000/hr
Operating Ambient Temp.(°C)	-10°C~55°C	-10°C~55°C
Storage Ambient Temp.(°C)	-20°C~60°C	-20°C~60°C
Package Dimension(mm)	31x31x611mm	31x31x1222mm
Outline Dimension(mm)	30x578mm	30x1198mm



LED Bulb 3W / E27

LED 球泡燈

Standard Housing Color: Black & White



Specifications:

Parameter	Min	Typ	Max	Units	Remark
LED Q'TY		6		ea	
Operation Voltage		9.6		V _{DC}	Constant Current 300mA
Ambient Temperature	-20		40	°C	
Power Consumption		3		Watt	
Illumination		200		Lm	Cool White: 5700K
			Warm White: 3000K		
LED Viewing Angle		120		Degree	
CRI		70			
LED Life time		30,000		hours	
Weight		95		g	
Outline dimension(mm)	105 × 60 (H × D)				



雄鑫電子

Super High-tech Electric Co., Ltd.

No.10, Ln. 158, Zhongshe 1st St., Longjing Dist., Taichung City 434, Taiwan R.O.C.

TEL:+886-4-2632-1227

n3044.Email@msa.hinet.net

